NSN 5910-01-217-8542

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-217-8542

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.530 inches
Body Width:
0.200 inches
Body Height:
0.320 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
6615-01-189-7976 gyroscope, displ
Capacitance Value Per Section:
0.082 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
0 0 71
400.0 dc single section
400.0 dc single section
400.0 dc single section Tolerance Range Per Section:
400.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section
400.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material:
400.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Plastic
400.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:
400.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 500000.0 megohms
400.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 500000.0 megohms Dissipation Factor At Reference Tempurature In Percent:
400.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 500000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.0500
400.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 500000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.0500 Terminal Surface Treatment:
400.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 500000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.0500 Terminal Surface Treatment: Solder
400.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 500000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.0500 Terminal Surface Treatment: Solder Terminal Type And Quantity:
400.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 500000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.0500 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
400.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 500000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.0500 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
400.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 500000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.0500 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a

No

NSN 5910-01-217-8542

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0