

View Online at <https://aerobasegroup.com/nsn/5910-01-217-8867>

**Body Style:**

Concentric

**Overall Height:**

Between 7.438 inches and 7.938 inches

**Shaft Diameter:**

0.469 inches single shaft and 0.531 inches single shaft

**Shaft Length:**

0.719 inches single shaft and 0.784 inches single shaft

**Alternating Current Rating In Amps:**

42.0

**Body Height:**

Between 6.719 inches and 7.157 inches

**Overall Diameter:**

Between 2.938 inches and 3.063 inches

**Center To Center Distance Between Terminals Parallel To Height:**

Between 3.485 inches and 3.891 inches

**Dissipation Factor At 25 Deg Celsius In Percent:**

0.001

**Adjustment Device Rotation:**

30.0 turns clockwise

**Adjustment Device Torque:**

Between 3.000 inch-ounces and 25.000 inch-ounces

**Mounting Facility Type And Quantity:**

2 terminal

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Shaft Type:**

Round single shaft

**Capacitance Range In Picofarads:**

+7.0/+1000.0 single section

**Nonderated Voltage Rating And Type:**

3000.0 ac peak single section

**Adjustment Device Drive Type And Quantity:**

1 shaft

**Material:**

Ceramic inclosure

**Test Data Document:**

81349-mil-c-23183 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 ferrule

**Specification Data:**

81349-mil-c-23183/5a government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0