NSN 5910-01-218-2309

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-218-2309

Body Style:
W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end
Reliability Indicator:
Not establishednot established
Terminal Length:
25.0 millimeters 25.0 millimeters 25.0 millimeters
Body Diameter:
8.5 millimeters
Body Length:
13.5 millimeters
Center To Center Distance Between Terminals Parallel To Diameter:
3.5 millimeters
Terminal Diameter:
0.61 millimeters
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Plain foil
Electrical Polarization:
Polarized
Capacitance Value Per Section:
33.000 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
63.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Equivalent Series Resistance At Reference Tempurature In Ohms:
0.84
Dc Leakage At Reference Temp:
11.000 microamperes
Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-218-2309

Electrolytic Fixed Capacitor - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0