## NSN 5910-01-218-3992

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-218-3992

<b>Body</b>	Stv	-ما
DUUV	OLV.	ıc.

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

0.150 inches 0.150 inches 0.150 inches

**Body Diameter:** 

0.265 inches

**Body Length:** 

0.500 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.250 inches

**Terminal Diameter:** 

Between 0.020 inches and 0.025 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

4.700 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

10.0 dc single section

**Tolerance Range Per Section:** 

-20.00/+20.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Tantalun

**Dissipation Factor At Reference Tempurature In Percent:** 

6.0000

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

1 50

Dc Leakage At Reference Temp:

0.500 microamperes

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-218-3992

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0