Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-218-4922

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

# Terminal Length:

Between 1.250 inches and 1.770 inches

#### **Body Diameter:**

Between 0.439 inches and 0.486 inches

#### **Body Length:**

2.814 inches

Terminal Diameter:

Between 0.024 inches and 0.036 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## **Electrical Polarization:**

Polarized

### Section Quantity:

1

## Capacitance Value Per Section:

100.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### **Criticality Code Justification:**

Feat

### **Tolerance Range Per Section:**

-15.00/+50.00 percent single section

### Capacitive Electrode Material:

Tantalum

### Dc Leakage At Reference Temp:

10.000 microamperes

### **Special Features:**

Item is hardness critical

### **Nuclear Hardness Critical Feature:**

Hardened

# **Terminal Type And Quantity:**

2 insulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5910-01-218-4922

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0