

View Online at <https://aerobasegroup.com/nsn/5910-01-218-7910>

**Body Style:**

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

**Reliability Indicator:**

Not established/not established/not established

**Terminal Length:**

0.500 inches 0.500 inches 0.500 inches

**Body Diameter:**

0.414 inches

**Body Length:**

0.670 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

Between 0.177 inches and 0.217 inches

**Terminal Diameter:**

Between 0.023 inches and 0.034 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Plain foil

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

220.000 microfarads single section

**Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

25.0 dc single section

**Tolerance Range Per Section:**

-10.00/+50.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.90

**Dc Leakage At Reference Temp:**

110.000 microamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0