

View Online at <https://aerobasegroup.com/nsn/5910-01-219-3466>

Body Style:

W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s) on one surface

Reliability Indicator:

Not establishednot establishednot established

Terminal Length:

1.000 inches 1.000 inches 1.000 inches

Body Length:

Between 0.160 inches and 0.185 inches

Body Width:

Between 0.195 inches and 0.225 inches

Body Height:

Between 0.060 inches and 0.075 inches

Center To Center Distance Between Terminals Parallel To Length:

0.150 inches

Terminal Diameter:

0.010 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Electrical Polarization:

Polarized

Capacitance Value Per Section:

10.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

6.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

6.0000

Dc Leakage At Reference Temp:

1.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Test Data Document:

81349-mil-c-49137 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-49137/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0