## NSN 5910-01-221-1703



Plastic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-221-1703 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Length:** 0.945 inches **Body Width:** 0.570 inches **Body Height:** 0.365 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.820 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Insulation Resistance At Maximum Operating Temp:** 20.0 megohm-microfarads **Capacitance Value Per Section:** 0.220 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -10.00 to 10.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 30000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polyester

Terminal Type And Quantity:

2 uninsulated wire lead

## NSN 5910-01-221-1703

Plastic Dielectric Fixed Capacitor - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0