## NSN 5910-01-222-5928

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-222-5928

### **Body Style:**

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

## **Reliability Indicator:**

Not establishednot establishednot established

### **Terminal Length:**

2.000 inches 2.000 inches 2.000 inches

#### **Body Diameter:**

0.875 inches

#### **Body Length:**

2.125 inches

#### Center To Center Distance Between Terminals Parallel To Length:

0.300 inches

**Terminal Diameter:** 

0.040 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

#### Plain foil

Impedance At Minimum Operating Tempurature In Ohms:

0.022

## **Electrical Polarization:**

Polarized

#### **End Application:**

Communication c an/tsq-111

#### Capacitance Value Per Section:

4500.000 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

16.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+75.00 percent single section

#### Case Material:

Metal

**Capacitive Electrode Material:** 

Aluminum

#### Equivalent Series Resistance At Reference Tempurature In Ohms:

0.039

**Terminal Surface Treatment:** 

Solder

#### **Case Insulation Material:**

Plastic

# NSN 5910-01-222-5928

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity:

2 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0