NSN 5910-01-222-9868

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-222-9868 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Length:** 1.300 inches **Body Width:** 0.250 inches **Body Height:** 0.750 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.719 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** 1055-01-167-4620 test program se **Insulation Resistance At Maximum Operating Temp:** 500.0 megohm-microfarads **Capacitance Value Per Section:** 0.082 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section **Tolerance Range Per Section:** -5.00 to 5.00 percent single section Case Material: **Plastic Insulation Resistance At Reference Temp:** 50000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.6000 **Terminal Surface Treatment:** Solder **Dielectric Material:**

Plastic polyethylene terephthalate

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-222-9868

Plastic Dielectric Fixed Capacitor - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0