NSN 5910-01-223-3970

Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-223-3970

| View Online at https://aerobasegroup.com/nsn/5910-01-223-3970 |
|--|
| Body Style: |
| W/o mtg facilities, terminals on opposite surfaces |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 2.000 inches |
| Body Length: |
| 2.062 inches |
| Body Width: |
| 0.250 inches |
| Body Height: |
| 1.200 inches |
| Terminal Diameter: |
| Between 0.038 inches and 0.042 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Insulation Resistance At Maximum Operating Temp: |
| 500.0 megohms |
| Capacitance Value Per Section: |
| 0.100 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 1500.0 dc single section |
| Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: |
| -3.0 to 6.0 single section |
| Tolerance Range Per Section: |
| -10.00 to 10.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 50000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.5000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5910-01-223-3970

Mica Dielectric Fixed Capacitor - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A010b0