## NSN 5910-01-223-9324

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-223-9324

## Body Style:

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not establishednot establishednot established

## Terminal Length:

1.500 inches 1.500 inches 1.500 inches

## Body Diameter:

0.351 inches

### **Body Length:**

0.786 inches

**Terminal Diameter:** 

0.025 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

## Anode Type:

Solid

**Electrical Polarization:** 

Polarized

#### **Features Provided:**

Hermetically sealed case

#### Capacitance Value Per Section:

100.000 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### Dc Leakage At Maximum Operating Temp:

200.0 microamperes

#### Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### Case Material:

Metal

#### **Capacitive Electrode Material:**

Tantalum

#### Dissipation Factor At Reference Tempurature In Percent:

8.0000

#### Dc Leakage At Reference Temp:

10.000 microamperes

#### **Case Insulation Material:**

Plastic

#### **Terminal Type And Quantity:**

2 insulated wire lead w/terminal lug

# NSN 5910-01-223-9324

Electrolytic Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0