

View Online at https://aerobasegroup.com/nsn/5910-01-224-0266

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

Body Length:

Between 0.280 inches and 0.300 inches

#### **Body Width:**

Between 0.280 inches and 0.300 inches

#### **Body Height:**

Between 0.080 inches and 0.100 inches

## Center To Center Distance Between Terminals Parallel To Length:

Between 0.185 inches and 0.215 inches

#### **Terminal Diameter:**

Between 0.024 inches and 0.029 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

## Capacitance Value Per Section:

220000.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0 to 15.0 without voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

## Criticality Code Justification:

Feat

## **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

100000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

2.5000

# **Terminal Surface Treatment:**

Solder

#### **Special Features:**

Burn-in test



# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0