## NSN 5910-01-224-1747

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-224-1747 **Body Style:** W/o mtg facilities, terminal (s) on one end **Reliability Indicator:** Not established **Terminal Length:** Between 0.281 inches and 0.375 inches **Body Diameter:** 0.500 inches **Body Length:** 1.165 inches **Continuous Current Rating In Amps:** 7.5 **Center To Center Distance Between Terminals Parallel To Diameter:** 0.200 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 220.000 microfarads single section **Nonderated Operating Temp:** Between 55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Case Insulation Material:** Plastic **Special Features:** Specially designed for high frequency applications; leads are awg 20 tin plated **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5910-01-224-1747

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0