## NSN 5910-01-224-1752

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-224-1752 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.1000 **Body Diameter:** 0.312 inches **Body Length:** 1.125 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 0.100 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Metal **Case Insulation Material:** Plastic **Test Data Document:** 81349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead **Specification Data:** 81349--39022/02-1222 government specification Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A010b0