NSN 5910-01-225-1281

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-225-1281

View Online at https://aerobasegroup.com/nsn/5910-01-225-1281	
Body Style:	
W/o mtg facilities terminal (s) on one surface	
Reliability Indicator:	
Not established	
Terminal Length:	
1.250 inches	
Body Length:	
0.150 inches	
Body Width:	
0.150 inches	
Body Height:	
0.070 inches	
Center To Center Distance Between Terminals Parallel To Length:	
0.100 inches	
Terminal Diameter:	
0.016 inches	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
Insulation Resistance At Maximum Operating Temp:	
10000.0 megohms	
Capacitance Value Per Section:	
15.000 picofarads single section	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 125.0 degrees celsius	
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius	:
0.0 single section	
Nonderated Continuous Voltage Rating And Type Per Section:	
100.0 dc single section	
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:	
-30.0 to 30.0 single section	
Tolerance Range Per Section:	
-5.00 to 5.00 percent single section	
Case Material:	
Plastic	
Insulation Resistance At Reference Temp:	
100000.0 megohms	
Quality Factor At Reference Temp:	
1000.0000	
Terminal Surface Treatment:	
Coldor	

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-225-1281

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



SI	1e	lf	Ιi	fe:
Ο.	···	•••	_,	٠٠.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0