## NSN 5910-01-225-1282

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-225-1282

| View Online at https://aerobasegroup.com/nsn/5910-01-225-1282              |
|--|
| Body Style:  |
| W/o mtg facilities terminal (s) on one surface                             |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| 1.250 inches   |
| Body Length:   |
| 0.100 inches   |
| Body Width:  |
| 0.100 inches   |
| Body Height:   |
| 0.070 inches   |
| Center To Center Distance Between Terminals Parallel To Length:            |
| 0.100 inches   |
| Terminal Diameter:   |
| 0.016 inches   |
| Schematic Diagram Designator:  |
| No common or grounded electrode (s)  |
| Insulation Resistance At Maximum Operating Temp:                           |
| 10000.0 megohms  |
| Capacitance Value Per Section:   |
| 2.200 picofarads single section  |
| Nonderated Operating Temp:   |
| Between -55.0 degrees celsius and 125.0 degrees celsius                    |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 0.0 single section   |
| Nonderated Continuous Voltage Rating And Type Per Section:                 |
| 100.0 dc single section  |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:   |
| -30.0 to 30.0 single section   |
| Tolerance Range Per Section:   |
| -0.10 to 0.10 picofarads single section                                    |
| Case Material:   |
| Plastic  |
| Insulation Resistance At Reference Temp:                                   |
| 100000.0 megohms   |
| Quality Factor At Reference Temp:  |
| 1000.0000  |
| Terminal Surface Treatment:  |
| Coldor   |

2 uninsulated wire lead

**Terminal Type And Quantity:** 

## NSN 5910-01-225-1282

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



| Shelf Life: |
|-------------|
|-------------|

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0