NSN 5910-01-225-1289

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-225-1289 | | | | |
|--|--|--|--|--|
| Body Style: | | | | |
| W/o mtg facilities terminal (s) on one surface | | | | |
| Reliability Indicator: | | | | |
| Not established | | | | |
| Terminal Length: | | | | |
| 1.250 inches | | | | |
| Body Length: | | | | |
| 0.150 inches | | | | |
| Body Width: | | | | |
| 0.150 inches | | | | |
| Body Height: | | | | |
| 0.070 inches | | | | |
| Center To Center Distance Between Terminals Parallel To Length: | | | | |
| 0.100 inches | | | | |
| Terminal Diameter: | | | | |
| 0.016 inches | | | | |
| Schematic Diagram Designator: | | | | |
| No common or grounded electrode (s) | | | | |
| Insulation Resistance At Maximum Operating Temp: | | | | |
| 10000.0 megohms | | | | |
| Capacitance Value Per Section: | | | | |
| 13.000 picofarads single section | | | | |
| Nonderated Operating Temp: | | | | |
| Between -55.0 degrees celsius and 125.0 degrees celsius | | | | |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: | | | | |
| 0.0 single section | | | | |
| Nonderated Continuous Voltage Rating And Type Per Section: | | | | |
| 50.0 dc single section | | | | |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: | | | | |
| -30.0 to 30.0 single section | | | | |
| Tolerance Range Per Section: | | | | |
| -2.00 to 2.00 percent single section | | | | |
| Case Material: | | | | |
| Plastic | | | | |
| Insulation Resistance At Reference Temp: | | | | |
| 100000.0 megohms | | | | |
| Quality Factor At Reference Temp: | | | | |
| 3000.0000 | | | | |
| Terminal Surface Treatment: | | | | |
| Coldor | | | | |

Terminal Type And Quantity: 2 uninsulated wire lead

NSN 5910-01-225-1289

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



| _ | | | | |
|---|-----|-----|---|------|
| c | hο | .1+ | | ife: |
| J | 116 | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0