NSN 5910-01-225-1296

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-225-1296

Padu Stulai
Body Style: W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length: 0.200 inches
Body Width:
0.200 inches
Body Height:
0.125 inches
Center To Center Distance Between Terminals Parallel To Length:
0.100 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
1000.0 megohms
Capacitance Value Per Section:
0.100 microfarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
-15.0 to 15.0 without voltage applied single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-5.00 to 5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
2.5000
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:

N/a

NSN 5910-01-225-1296

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



	• •					
ın	18	<i>(</i>)+	Me	20	III	ω.

--

Demilitarization:

No

Fiig:

A010b0