NSN 5910-01-225-1954



Electrolytic Fixed Capacitor - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5910-01-225-1954
Body Style:
W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surface
Reliability Indicator:
Not establishednot established
Terminal Length:
0.600 inches 0.600 inches
Body Length:
0.287 inches
Body Width:
0.185 inches
Body Height:
0.165 inches
Center To Center Distance Between Terminals Parallel To Length:
0.100 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid

Electrical Polarization:

Polarized

Capacitance Value Per Section:

1.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

35.0 dc single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Tempurature In Percent:

6.0000

Dc Leakage At Reference Temp:

1.000 microamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-225-1954

Electrolytic Fixed Capacitor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0