## NSN 5910-01-226-3578

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-226-3578

Body Style:
W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end
Reliability Indicator:
Not establishednot established
Terminal Length:
0.787 inches 0.787 inches 0.787 inches
Body Diameter:
0.197 inches
Body Length:
0.433 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.078 inches
Terminal Diameter:
0.019 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Plain foil
Impedance At Minimum Operating Tempurature In Ohms:
3.0
Electrical Polarization:
Polarized
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Dissipation Factor At Reference Tempurature In Percent:
10.0000
Dc Leakage At Reference Temp:

Solder

**Case Insulation Material:** 

**Terminal Surface Treatment:** 

4.000 microamperes

Plastic

## NSN 5910-01-226-3578

Electrolytic Fixed Capacitor - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0