

View Online at <https://aerobasegroup.com/nsn/5910-01-226-3579>

**Body Style:**

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end

**Reliability Indicator:**

Not established/not established

**Terminal Length:**

0.787 inches 0.787 inches

**Body Diameter:**

0.512 inches

**Body Length:**

0.787 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

0.196 inches

**Terminal Diameter:**

0.023 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Plain foil

**Impedance At Minimum Operating Temperature In Ohms:**

3.0

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

330.000 microfarads single section

**Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

10.0000

**Dc Leakage At Reference Temp:**

4.000 microamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0