## NSN 5910-01-226-5584

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-226-5584

**Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Length:** 0.200 inches **Body Width:** 0.200 inches **Body Height:** 0.100 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.169 inches and 0.231 inches **Terminal Diameter:** Between 0.015 inches and 0.020 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:** 

10000.0 megohms

**Capacitance Value Per Section:** 

30.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-80.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** 

-30.0 to 30.0 single section

**Tolerance Range Per Section:** 

-5.00 to 5.00 percent single section

**Case Material:** 

Plastic

**Insulation Resistance At Reference Temp:** 

100000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

2.500

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-226-5584

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



She	١f	Ιi	f۵	•
0	•••			•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0