

View Online at <https://aerobasegroup.com/nsn/5910-01-226-8309>

**Body Style:**

W/o mtg facilities, terminals on opposite surfacesw/o mtg facilities, terminals on opposite surfacesw/o mtg facilities, terminals on opposite surfaces

**Mil-std-1276 Wire Lead Type Designator:**

N-4n-4n-4

**Reliability Indicator:**

Not establishednot establishednot established

**Terminal Length:**

Between 1.500 inches and 1.500 inches and 1.500 inches and 1.750 inches 1.750 inches 1.750 inches

**Body Length:**

0.475 inches

**Body Width:**

0.150 inches

**Body Height:**

0.375 inches

**Terminal Diameter:**

0.016 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

22.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

35.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

8.0000

**Dc Leakage At Reference Temp:**

9.000 microamperes

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0