NSN 5910-01-227-5315

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-227-5315

view Offiline at https://aerobasegroup.com/hsi//3510-01-221-3515
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
2.250 inches
Body Length:
1.050 inches
Body Width:
0.755 inches
Body Height:
0.418 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.880 inches and 0.920 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
7000.0 megohms
Capacitance Value Per Section:
0.680 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
150.0 ac-rms single section and 250.0 dc single section
Criticality Code Justification:
Feat
Tolerance Range Per Section:
-10.00 to 10.00 percent single section
Case Material:
Plastic
Dissipation Factor At Reference Tempurature In Percent:
0.300
Terminal Surface Treatment:
Solder
Special Features:
Burn-in test
Terminal Type And Quantity:
2 uninsulated wire lead

N/a

Shelf Life:

NSN 5910-01-227-5315

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A010b0