NSN 5910-01-227-9095

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-227-9095

| Body | Stv | le٠ |
|------|-----|-----|
| Bouv | JLV | ıc. |

W/thd bushing mtg, terminal(s) on one endw/thd bushing mtg, terminal(s) on one

Reliability Indicator:

Not establishednot established

Terminal Length:

0.438 inches 0.438 inches 0.438 inches

Body Diameter:

1.375 inches

Body Length:

2.750 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Impedance At Minimum Operating Tempurature In Ohms:

42.0

Electrical Polarization:

Polarized

Mounting Facility Screw Thread Series Designator:

Un

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

350.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.875 inches

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dissipation Factor At Reference Tempurature In Percent:

25.0000

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

NSN 5910-01-227-9095

Electrolytic Fixed Capacitor - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0