Glass Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-227-9646

Rody	Style:
Chip t	-
	bility Indicator: stablished
	inal Length:
	een 0.060 inches and 0.090 inches
-	Length:
	een 0.120 inches and 0.150 inches
-	Width:
	een 0.065 inches and 0.100 inches
	Height:
	een 0.095 inches and 0.125 inches
	matic Diagram Designator:
	mmon or grounded electrode (s)
	ation Resistance At Maximum Operating Temp:
	00.0 megohms
•	citance Value Per Section:
	0 picofarads single section
	erated Operating Temp:
	een -55.0 degrees celsius and 125.0 degrees celsius
Temp	urature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
90.0 s	single section
Nond	erated Continuous Voltage Rating And Type Per Section:
200.0	dc single section
Tolera	ance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-20.0 1	to 20.0 single section
Tolera	ance Range Per Section:
-5.00 1	to 5.00 percent single section
Case	Material:
Glass	
Insula	ation Resistance At Reference Temp:
10000	000.0 megohms
Qualit	ty Factor At Reference Temp:
4444.0	000
Termi	inal Surface Treatment:
Silver	
Precio	ous Material And Location:
Termi	nal surfaces silver
Termi	inal Type And Quantity:
2 ribbo	on
Shelf	Life:
N/a	

Glass Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0