

View Online at <https://aerobasegroup.com/nsn/5910-01-228-0569>

Body Style:

Chip typechip typechip typechip type

Reliability Indicator:

Establishedestablishedestablishedestablished

Reliability Failure Rate Level In Percent:

0.10000.10000.10000.1000

Terminal Length:

0.030 inches 0.030 inches 0.030 inches 0.030 inches

Body Length:

0.220 inches 0.220 inches

Body Width:

0.135 inches 0.135 inches

Body Height:

0.070 inches 0.070 inches

Schematic Diagram Designator:

No common or grounded electrode (s)no common or grounded electrode(s)

Anode Type:

Solidsolid

Electrical Polarization:

Polarizedpolarized

Capacitance Value Per Section:

4.700 microfarads single section4.700 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and -55.0 degrees celsius and 85.0 degrees celsius 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

20.0 microampere20.0 microampere

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section25.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section-10.00/+10.00 percent single section

Case Material:

Ceramicceramic

Capacitive Electrode Material:

Tantalumtantalum

Dissipation Factor At Reference Temperature In Percent:

6.00006.0000

Dc Leakage At Reference Temp:

2.000 microampere2.000 microampere

Terminal Surface Treatment:

Solder

Precious Material And Location:

Terminals goldterminals gold

Test Data Document:

81349-mil-c-55365 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 bonding pad

Specification Data:

81349-mil-c-55365/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0