Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-228-0569

# Body Style:

Chip typechip typechip typechip type

# **Reliability Indicator:**

 ${\sf Establishedestablishedestablished}$ 

# Reliability Failure Rate Level In Percent:

0.10000.10000.10000.1000

# Terminal Length:

0.030 inches 0.030 inches 0.030 inches 0.030 inches

## **Body Length:**

0.220 inches 0.220 inches

# Body Width:

0.135 inches 0.135 inches

Body Height:

0.070 inches 0.070 inches

Schematic Diagram Designator:

No common or grounded electrode (s)no common or grounded electrode(s)

Anode Type:

Solidsolid

#### **Electrical Polarization:**

Polarizedpolarized

### Capacitance Value Per Section:

4.700 microfarads single section4.700 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and -55.0 degrees celsius and 85.0 degrees celsius 85.0 degrees celsius

### Dc Leakage At Maximum Operating Temp:

20.0 microamperes20.0 microamperes

### Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section25.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section-10.00/+10.00 percent single section

#### **Case Material:**

Ceramicceramic

#### **Capacitive Electrode Material:**

Tantalumtantalum

### Dissipation Factor At Reference Tempurature In Percent:

6.00006.0000

## Dc Leakage At Reference Temp:

2.000 microamperes2.000 microamperes

## **Terminal Surface Treatment:**

Solder

#### **Precious Material And Location:**

Terminals goldterminals gold

Electrolytic Fixed Capacitor - Page 2 of 2



#### **Test Data Document:**

81349-mil-c-55365 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 bonding pad
Specification Data:
81349-mil-c-55365/4 government specification
Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No
Fiig:
A010b0