NSN 5910-01-228-0571

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-228-0571

D ~ d	Style:
DUUV	Sivie.

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not establishednot established

Terminal Length:

0.248 inches 0.248 inches 0.248 inches

Body Diameter:

1.398 inches

Body Length:

1.181 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.394 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Impedance At Minimum Operating Tempurature In Ohms:

0.1

Electrical Polarization:

Polarized

Capacitance Value Per Section:

4700.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-10.00/+30.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Equivalent Series Resistance At Reference Tempurature In Ohms:

0.079

Dc Leakage At Reference Temp:

3.000 milliamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 printed circuit

NSN 5910-01-228-0571

Electrolytic Fixed Capacitor - Page 2 of 2



_			-		
C	hο	14		.ife	•
•			_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0