NSN 5910-01-228-8732

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-228-8732

Body Style: Piston Overall Length: 0.460 inches Terminal Length: 0.400 inches Body Length: 0.300 inches Body Length: 0.300 inches Overall Diameter: Between 0.275 inches and 0.295 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: -15.0 to 15.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	
Overall Length: 0.460 inches Terminal Length: 0.400 inches Body Length: 0.300 inches Overall Diameter: Between 0.275 inches and 0.295 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: -15.0 to 15.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Body Style:
Terminal Length: 0.400 inches Body Length: 0.300 inches Body Length: 0.300 inches Overall Diameter: Between 0.275 inches and 0.295 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: -15.0 to 15.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Piston
Terminal Length: 0.400 inches Body Length: 0.300 inches Overall Diameter: Between 0.275 inches and 0.295 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: -15.0 to 15.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 de continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Overall Length:
0.400 inches Body Length: 0.300 inches Overall Diameter: Between 0.275 inches and 0.295 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: -15.0 to 15.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	0.460 inches
Body Length: 0.300 inches Overall Diameter: Between 0.275 inches and 0.295 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: -15.0 to 15.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Terminal Length:
Overall Diameter: Between 0.275 inches and 0.295 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: -15.0 to 15.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	0.400 inches
Overall Diameter: Between 0.275 inches and 0.295 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: -15.0 to 15.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 1000000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Body Length:
Between 0.275 inches and 0.295 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: -15.0 to 15.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	0.300 inches
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: -15.0 to 15.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Overall Diameter:
0.0 single section Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: -15.0 to 15.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Between 0.275 inches and 0.295 inches
Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: -15.0 to 15.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	0.0 single section
Center To Center Distance Between Terminals Parallel To Length: 0.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:
O.265 inches Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	-15.0 to 15.0 single section
Quality Factor At 25 Deg Celsius: 5000.0 Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Center To Center Distance Between Terminals Parallel To Length:
Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	0.265 inches
Inclosure Type: Encased Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Quality Factor At 25 Deg Celsius:
Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	5000.0
Tuning Characteristic: Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Inclosure Type:
Straight line capacity single section Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Encased
Adjustment Device Torque: Between 1.000 inch-ounces and 5.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Tuning Characteristic:
Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Straight line capacity single section
Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Adjustment Device Torque:
Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Between 1.000 inch-ounces and 5.000 inch-ounces
Insulation Dc Resistance At Max Operating Temp: 100000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Insulation Dc Resistance At 25 Deg Celsius:
Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	1000000.0 megohms
Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Insulation Dc Resistance At Max Operating Temp:
2 terminal Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	100000.0 megohms
Nonderated Operating Temp: Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Mounting Facility Type And Quantity:
Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	2 terminal
Capacitance Range In Picofarads: +1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Nonderated Operating Temp:
+1.0 to 10.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Between -65.0 degrees celsius and 125.0 degrees celsius
Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Capacitance Range In Picofarads:
250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	+1.0 to 10.0 single section
Adjustment Device Drive Type And Quantity: 1 slotted screw Special Features: High reliability	Nonderated Voltage Rating And Type:
1 slotted screw Special Features: High reliability	250.0 dc continuous single section
Special Features: High reliability	Adjustment Device Drive Type And Quantity:
High reliability	1 slotted screw
	Special Features:
	High reliability
Terminal Type And Quantity:	Terminal Type And Quantity:

2 printed circuit

NSN 5910-01-228-8732

Air Dielectric Variable Capacitor - Page 2 of 2



Shelf	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0