## NSN 5910-01-228-9750

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-228-9750

| D | _ | ۵, |   | 0 | ٠  |   |    |  |
|---|---|----|---|---|----|---|----|--|
| D | u | u  | v | J | ιν | ш | e: |  |

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

## **Reliability Indicator:**

Not establishednot established

**Terminal Length:** 

0.248 inches 0.248 inches 0.248 inches

**Body Diameter:** 

0.984 inches

**Body Length:** 

1.181 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.394 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Impedance At Minimum Operating Tempurature In Ohms:** 

12.0

**Electrical Polarization:** 

Polarized

**End Application:** 

4920-01-111-2981 automatic test

**Capacitance Value Per Section:** 

220.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Range Per Section:** 

-20.00/+20.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Dissipation Factor At Reference Tempurature In Percent:** 

10.000

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

0.61

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

## NSN 5910-01-228-9750

Electrolytic Fixed Capacitor - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 2 printed circuit           |

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0