

View Online at <https://aerobasegroup.com/nsn/5910-01-228-9751>

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

1.000

Terminal Length:

1.250 inches

Body Length:

0.190 inches

Body Width:

0.200 inches

Body Height:

0.090 inches

Center To Center Distance Between Terminals Parallel To Length:

0.200 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Insulation Resistance At Maximum Operating Temp:

7000.0 megohms

Capacitance Value Per Section:

0.0033 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc single section

Tolerance Range Per Section:

-2.00/+2.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

500000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

0.300

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-55514/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0