

View Online at <https://aerobasegroup.com/nsn/5910-01-229-0118>

**Body Style:**

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Reliability Indicator:**

Establishedestablishedestablished

**Reliability Failure Rate Level In Percent:**

1.0001.0001.000

**Terminal Length:**

Between 2.250 inches and 2.250 inches and 2.250 inches and 2.750 inches 2.750 inches 2.750 inches

**Body Diameter:**

0.785 inches

**Body Length:**

Between 1.625 inches and 1.843 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

Between 0.150 inches and 0.450 inches

**Terminal Diameter:**

Between 0.038 inches and 0.048 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Impedance At Minimum Operating Temperature In Ohms:**

0.322

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

550.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

440.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

40.0 dc single section

**Tolerance Range Per Section:**

-10.00/+75.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.48

**Dc Leakage At Reference Temp:**

74.000 microamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Test Data Document:**

81349-mil-c-39018 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 uninsulated wire lead

**Specification Data:**

81349-mil-c-39018/7 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0