## NSN 5910-01-229-2700

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-229-2700

Body Style:
W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals
Reliability Indicator:
Not establishednot established
Terminal Length:
1.500 inches 1.500 inches 1.500 inches
Body Diameter:
0.135 inches
Body Length:
0.286 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Electrical Polarization:
Polarized
Capacitance Value Per Section:
0.047 microfarads single section
Nonderated Operating Temp:
Between -80.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
6.000
Dc Leakage At Reference Temp:
1.500 microamperes
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:

N/a

## NSN 5910-01-229-2700

Electrolytic Fixed Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A010b0