

View Online at https://aerobasegroup.com/nsn/5910-01-229-5558

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

1.0000

**Terminal Length:** 

Between 1.625 inches and 2.625 inches

### **Body Diameter:**

Between 0.665 inches and 0.685 inches

### **Body Length:**

Between 1.844 inches and 1.906 inches

### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

### Capacitance Value Per Section:

0.680 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

## Tolerance Range Per Section:

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

75000.0 megohm-microfarads

## **Dissipation Factor At Reference Tempurature In Percent:**

0.1500

## Test Data Document:

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-19978/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A010b0