## NSN 5910-01-230-0400

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-230-0400

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one end

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

0.063 inches 0.063 inches

**Body Diameter:** 

1.453 inches

**Body Length:** 

3.250 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.500 inches

**Terminal Diameter:** 

0.190 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Electrical Polarization:** 

Polarized

**End Application:** 

4920-01-111-6823 test set, semi-a

**Capacitance Value Per Section:** 

2800.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

15000.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

75.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+75.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

0 16

Dc Leakage At Reference Temp:

6000.000 microamperes

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

2 threaded hole

## NSN 5910-01-230-0400

Electrolytic Fixed Capacitor - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0