Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-230-4459

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

## **Reliability Indicator:**

Not established

# Terminal Length:

1.000 inches

## **Body Length:**

1.000 inches

### **Body Width:**

1.040 inches

### **Body Height:**

### 0.400 inches

# Center To Center Distance Between Terminals Parallel To Length:

0.800 inches

### **Terminal Diameter:**

0.031 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## **Capacitance Value Per Section:**

0.120 microfarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

650.0 dc single section

# Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:

-1.0 to 1.0 single section

### **Tolerance Range Per Section:**

-5.00 to 5.00 percent single section

### **Case Material:**

Plastic

### Insulation Resistance At Reference Temp:

200000.0 megohms

# **Dissipation Factor At Reference Tempurature In Percent:**

1.000

# **Terminal Surface Treatment:**

Solder

# **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

## Unit Of Measure:

---

Mica Dielectric Fixed Capacitor - Page 2 of 2

Demilitarization:

No

Fiig:

A010b0

