NSN 5910-01-230-7843

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-230-7843 **Body Style:** W/mtg bracket, terminal (s) on one end **Reliability Indicator:** Not established **Terminal Length:** 1.260 inches **Body Length:** Between 0.180 inches and 0.200 inches **Body Width:** Between 0.180 inches and 0.200 inches **Body Height:** Between 0.080 inches and 0.100 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 6.800 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -0.25/+0.25 picofarads single section Case Material: Ceramic

Test Data Document:

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-20/35 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Denninanzanon

No

Fiig:

A010b0