NSN 5910-01-231-1316

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-231-1316

| Body Style: |
|---|
| W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 2.000 inches 2.000 inches 2.000 inches |
| Body Diameter: |
| 0.375 inches |
| Body Length: |
| 1.250 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Etched foil |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 200.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Terminal Surface Treatment: |
| Solder |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

No

Demilitarization:

NSN 5910-01-231-1316

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0