## NSN 5910-01-231-1470

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-231-1470

**Body Style:** 

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

**Terminal Length:** 

Between 1.500 inches and 2.000 inches

**Body Diameter:** 

0.875 inches

**Body Length:** 

3.687 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

Between 0.150 inches and 0.400 inches

**Terminal Diameter:** 

Between 0.037 inches and 0.043 inches

**Schematic Diagram Designator:** 

Electrod (s) grounded to case

**Anode Type:** 

Plain foil

**Impedance At Minimum Operating Tempurature In Ohms:** 

0.021

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

1800.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 105.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:** 

900.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+50.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

0.042

Dc Leakage At Reference Temp:

150.000 microamperes

**Terminal Surface Treatment:** 

Solder

## NSN 5910-01-231-1470

Electrolytic Fixed Capacitor - Page 2 of 2



Case Insulation Material:
Plastic
Terminal Type And Quantity
3 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0