## NSN 5910-01-231-2464

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-231-2464

View Online at https://aerobasegroup.com/nsn/5910-01-231-2464
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length:
0.550 inches
Body Width:
0.375 inches
Body Height:
0.250 inches
Center To Center Distance Between Terminals Parallel To Length:
0.400 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
5820-01-144-6007 receiver, radio
Capacitance Value Per Section:
0.0022 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
-200.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-30.0 to 30.0 single section
Tolerance Range Per Section:
-1.00 to 1.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
1000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
0.150
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:

2 uninsulated wire lead

## NSN 5910-01-231-2464

Plastic Dielectric Fixed Capacitor - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0