NSN 5910-01-231-2469

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-231-2469

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
0.562 inches
Body Length:
0.130 inches
Body Width:
0.110 inches
Body Height:
0.065 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
5820-01-082-0814 amplifier-frequ
Insulation Resistance At Maximum Operating Temp:
10000.0 megohms
Capacitance Value Per Section:
82000.000 picofarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
-15.0 to 15.0 without voltage applied single section
-15.0 to 15.0 without voltage applied single section Nonderated Operating Temp:
·
Nonderated Operating Temp:
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section:
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material:
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Ceramic
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp:
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent:
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.500
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.500 Terminal Surface Treatment:
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.500 Terminal Surface Treatment: Silver
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00 to 10.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 2.500 Terminal Surface Treatment: Silver Precious Material And Location:

N/a

Shelf Life:

NSN 5910-01-231-2469

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0