NSN 5910-01-231-8340

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-231-8340

Body Style:
W/thd body mtg, axial terminals
Reliability Indicator:
Not established
Terminal Length:
0.750 inches
Body Diameter:
0.875 inches
Body Length:
0.750 inches
Terminal Diameter:
0.164 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Screw Thread Series Designator:
Unef
Mounting Facility Type And Quantity:
1 threaded bushing
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
100.0 megohm-microfarads
Capacitance Value Per Section:
0.010 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Thread Size:
0.625 inches
Nonderated Continuous Voltage Rating And Type Per Section:
250.0 ac-rms single section and 400.0 dc single section
Tolerance Range Per Section:
-20.00 to 20.00 percent single section
Thread Tolerance Class:
2a external
Case Material:
Metal
Insulation Resistance At Reference Temp:
20000.0 megohm-microfarads
Power Factor At Reference Tempurature In Percent:
1.000
Terminal Type And Quantity:

2 threaded hole

NSN 5910-01-231-8340

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0