NSN 5910-01-231-8416

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-231-8416				
Body Style:				
W/o mtg facilities terminal (s) on one surface				
Reliability Indicator:				
Not established				
Terminal Length:				
1.625 inches				
Body Length:				
0.290 inches				
Body Width:				
0.245 inches				
Body Height:				
0.095 inches				
Center To Center Distance Between Terminals Parallel To Length:				
0.200 inches				
Terminal Diameter:				
0.020 inches				
Schematic Diagram Designator:				
No common or grounded electrode (s)				
Capacitance Value Per Section:				
0.0047 microfarads single section				
Nonderated Operating Temp:				
Between -55.0 degrees celsius and 125.0 degrees celsius				
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:				
0.0 single section				
Nonderated Continuous Voltage Rating And Type Per Section:				
50.0 dc single section				
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:				
-150.0 to 50.0 single section				
Tolerance Range Per Section:				
-5.00 to 5.00 percent single section				
Case Material:				
Plastic				
Insulation Resistance At Reference Temp:				
500000.0 megohms				
Dissipation Factor At Reference Tempurature In Percent:				
0.300				
Terminal Surface Treatment:				
Solder				
Terminal Type And Quantity:				
2 uninsulated wire lead				

Shelf Life: N/a

NSN 5910-01-231-8416

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	nit	O+	Measure:
u		v	wicasuic.

--

Demilitarization:

No

Fiig:

A010b0