

View Online at <https://aerobasegroup.com/nsn/5910-01-232-0964>

**Body Style:**

Dual inline

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.100

**Terminal Length:**

0.148 inches

**Body Length:**

0.092 inches

**Body Width:**

0.260 inches

**Body Height:**

0.283 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.325 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

1260-01-208-6448 mast mounted si

**Insulation Resistance At Maximum Operating Temp:**

10000.0 megohms

**Capacitance Value Per Section:**

1000000.000 picofarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-40.0 to 15.0 with rated voltage applied single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

1000000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

3.000

**Terminal Surface Treatment:**

Solder

**Test Data Document:**

81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 printed circuit

**Specification Data:**

81349-mil-c-39014/22 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0