

View Online at <https://aerobasegroup.com/nsn/5910-01-232-4559>

Body Style:

Chip typechip typechip typechip type

Reliability Indicator:

Establishedestablishedestablishedestablished

Reliability Failure Rate Level In Percent:

0.1000.1000.1000.100

Terminal Length:

0.050 inches 0.050 inches 0.050 inches 0.050 inches

Body Length:

0.265 inches 0.265 inches

Body Width:

0.110 inches 0.110 inches

Body Height:

0.110 inches 0.110 inches

Center To Center Distance Between Terminals Parallel To Length:

0.215 inches 0.215 inches

Schematic Diagram Designator:

No common or grounded electrode (s)no common or grounded electrode(s)

Electrical Polarization:

Polarizedpolarized

End Application:

1260-01-208-6448 mast mounted si1260-01-208-6448 mast mounted si

Capacitance Value Per Section:

22.000 microfarads single section22.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and -55.0 degrees celsius and 85.0 degrees celsius 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

40.0 microamperes40.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section15.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section-10.00/+10.00 percent single section

Case Material:

Ceramicceramic

Capacitive Electrode Material:

Tantalumtantalum

Dissipation Factor At Reference Temperature In Percent:

8.0008.000

Dc Leakage At Reference Temp:

4.000 microamperes4.000 microamperes

Terminal Surface Treatment:

Gold

Precious Material And Location:

Terminal surfaces goldterminal surfaces gold

Test Data Document:

81349-mil-c-55365 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 bonding pad

Specification Data:

81349-mil-c-55365/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0