

View Online at <https://aerobasegroup.com/nsn/5910-01-232-4559>

**Body Style:**

Chip typechip typechip typechip type

**Reliability Indicator:**

Establishedestablishedestablishedestablished

**Reliability Failure Rate Level In Percent:**

0.1000.1000.1000.100

**Terminal Length:**

0.050 inches 0.050 inches 0.050 inches 0.050 inches

**Body Length:**

0.265 inches 0.265 inches

**Body Width:**

0.110 inches 0.110 inches

**Body Height:**

0.110 inches 0.110 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.215 inches 0.215 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)no common or grounded electrode(s)

**Electrical Polarization:**

Polarizedpolarized

**End Application:**

1260-01-208-6448 mast mounted si1260-01-208-6448 mast mounted si

**Capacitance Value Per Section:**

22.000 microfarads single section22.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and -55.0 degrees celsius and 85.0 degrees celsius 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

40.0 microamperes40.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

15.0 dc single section15.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section-10.00/+10.00 percent single section

**Case Material:**

Ceramicceramic

**Capacitive Electrode Material:**

Tantalumtantalum

**Dissipation Factor At Reference Tempurature In Percent:**

8.0008.000

**Dc Leakage At Reference Temp:**

4.000 microamperes4.000 microamperes

**Terminal Surface Treatment:**

Gold

**Precious Material And Location:**

Terminal surfaces goldterminal surfaces gold

**Test Data Document:**

81349-mil-c-55365 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 bonding pad

**Specification Data:**

81349-mil-c-55365/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0