NSN 5910-01-232-5612

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-232-5612

g
Body Style:
W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one end
Reliability Indicator:
Not establishednot established
Terminal Length:
1.500 inches 1.500 inches
Body Diameter:
0.175 inches
Body Length:
0.350 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.250 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Electrical Polarization:
Polarized
Capacitance Value Per Section:
2.200 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
35.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
5.000
Dc Leakage At Reference Temp:
1.200 microamperes
Terminal Surface Treatment:

Shelf Life:

Terminal Type And Quantity:

2 uninsulated wire lead

Solder

N/a

NSN 5910-01-232-5612

Electrolytic Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0