Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-232-6045

### **Reliability Indicator:**

Established

### **Reliability Failure Rate Level In Percent:**

1.0000

# **Terminal Length:**

1.500 inches

### **Body Diameter:**

0.219 inches

#### **Body Length:**

0.453 inches

#### **Terminal Diameter:**

0.025 inches

### **Electrical Polarization:**

Polarized

### Capacitance Value Per Section:

22.000 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

# Tolerance Range Per Section:

-10.00/+10.00 percent single section

### **Test Data Document:**

81349-mil-c-39006 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

### Unit Of Measure:

```
--
```

Demilitarization:

No

Fiig:

A010b0

Mil-std (military Standard):

Mil-c-39006 spec.